

ADDITIONAL INSTALLED EQUIPMENT LIST

Description	Condition Rating		
	Very Good	Average	Minimum
RADIO TELEMETRY			
Unit (RTU) (Master)	33,860	23,650	5,910
(Large)	8,060	3,700	920
(Small)	5,480	2,250	560
Cathodic Protection Unit			
with Rectifier	1,460	740	180
with Solar Panels	6,720	2,770	690
Gas Meter Run with House	4,170	2,280	680
LACT Unit	18,050	9,260	2,310
Gas Booster Line			
Compressor (15-30 H.P.)	22,120	10,760	2,690
In-Line Heater	5,900	2,970	740
Triplex Water Injection Pump			
75 H.P. Electric Motor	19,260	9,950	2,280
Chemical Pump	1,060	530	240
Recycle Pump	1,110	690	170
Chemical tanks (55-125 Gal.)	1,200	670	240
Fuel/Chemical Tanks (500 Gal.)	4,190	2,310	840
Pit Tanks	8,570	4,710	1,710
Water Flow Lines (per foot)	5.48	3.01	1.08
Separators :			
48" x 12' High Pressure	22,010	12,100	4,400
30" x 10' High Pressure	17,000	9,350	3,400
Free Water Knockouts			
30" x 10'	3,980	2,390	600
4" x 10'	5,810	3,490	870
6" x 10'	6,720	4,020	1,000
8" x 10'	9,450	5,600	1,400
4" x 15'	6,220	3,730	940
6" x 15'	7,600	4,550	1,140
Dehydrator			
Average of All Sizes	14,630	8,510	2,130
Wellheads			
Flanged Wellhead (Total Value)*	5,130	1,850	650
Threaded Wellhead (Total Value)*	1,340	810	220
Flanged Wellhead (Differential)**	3,780	1,040	430
Flanged/Threaded Combo (Differential)**	2,270	910	350

*For use only with wells having dual wellheads on the same wellbore.

**For use only in Basins where Threaded Wellheads are typical. (See VALUATION PROCEDURES.)

Description	Condition Rating		
	Very Good	Average	Minimum
Vapor Recovery System	15,590	9,350	2,340
Vapor Flare System (Enclosed Stack)	10,750	6,450	1,610
Sound Panels (Galvanized Steel):			
Wall & Roof Panels/Sq.Ft. (Padded)	3.36	2.69	0.68
Scrubber	2,600	1,430	520
<u>Waste Oil Recycling Operations Only:</u>			
Tank (1) 300 BBL	6,330	3,160	1,450
Separator 30" x 10' Vertical	5,170	2,490	620
Separator 24" x 10' Horizontal	8,120	4,260	1,060